
NOTES:

- 1 FREE SPEED 700 RPM
- 2 MAX TORQUE 38 NM
- 3 WEIGHT 3.16 LBS / 1.4 KG
- 4 OUTPUT 3/8" SQ. DRIVE

REVISIONS											
REV.	DESCRIPTION	ECN	DATE	BY	APPRVD						
Α	PRODUCTION RELEASE		5-23-01	JFB	PP						









PRINTED COPIES OF THIS DOCUMENT ARE COL WITH PURCHASING OR THE DOCUMENT COC								
THIS DRAWING EMODOLES CONFIDENTIAL INFORMATION OF A KARBOYNE IN CORPORATED. IN THE ABSENCE OF EXPRESSED WRITTER PERMISSION, ACRADYNE HAS LOANED THIS COPY UNITS THE UNDEST SHOWING THAT. A IT WOULD BE USED FOR ANY PURPOSE EXCEPT THAT FOR WHICH THIS SLOANED, BIOTATA	DRAWN	JFB 5-23-01	& AcraDyne				CRADYNE INC. 1204 E. MAPLE MI. 48083 U.S.A.	
CONTAINED THEREIN SHALL NOT BE DISCLOSED TO OTHERS, C) IT WILL NOT BE REPRODUCED. D) IT WILL BE RETURNED ON DEMAND TO ACRADYNE INC.	CHECKED	KJD	OUTLINE - AEM 2038					
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES DIMENSIONS AND TOLERANCES PER ANSI Y14.5	APPROVED	PP	2000 SERIES TRIPLE STEP 3/8 DR.					
SURFACE ROUGHNESS PER ANSI Y14.36 TOLERANCES ON DECIMALS: X = ±300	PROJECT NO.	2000	SIZE	21505		DRAWING NO. 21505		
ANGLE = ±0° 30' REMOVE BURRS AND SHARP EDGES .015R. MAX. MACHINE SURFACE FINISH: 125 RMS OR BETTER	DO NOT SO	CALE DRAWING	SCALE	1:1	SHEET OF 1	1	REVISION	Α